## 







#### Full LED Lighting

The CB500F features an all-LED lighting system for optimal energy effciency. The slick headlights design provide the CB500F with contemporary design edge.



#### Assist / Slipper Clutch

Shifting through the six-speed gearbox on the CB500F has been made easy with assist / slipper clutch feature. It will assist the rider to attack a corner in the full confident without the fear of locking up the rear





#### Cockpit Control

The CB500F features a concise Liquid Crystal Display (LCD) odometer panel which display speed and rev counter, dual trip



#### Anti-Lock Brake System (ABS)

The new CB500F features a single front 310mm wavy disc and powerful two-piston brake caliper matched to a 240mm rear disc and single piston caliper. Dual channel ABS





#### Twin-Cylinder Engine

The 8-valve, liquid-cooled parallel twincylinder engine produces 37kW @ 8,500rpm with a peak torque of 45Nm @ 6,500rpm. Revised camshaft and valve lift have increased low- and mid-range torque for



Emergency Stop Signal

The CB500F's Emergency Stop Signal system detects sudden braking and automatically activates the front and rear hazard lights, which flash to warn any nearby vehicles



## **SPECIFICATIONS**

ENGINE AND FUEL SYSTEM	
Engine Type	Liquid-Cooled, 4 Stroke, DOHC
Displacement	471 cm <sup>3</sup>
Bore x Stroke	67.0 mm x 66.8 mm
Compression Ratio	10.7 : 1
Max. Power	37 kW @ 8,500 rpm
Max. Torque	45 N.m @ 6,500 rpm
Engine Oil Capacity	3.2 ℓ
Carburation	PGM-FI
TRANSMISSION	
Clutch Type	Assist / Slipper Clutch, Wet Multiplate Type
Transmission Type	6 Speed, Mechanical (Chain drive)

DIMENSION AND WEIGHT	
Dimensions (L x W x H)	2,080 mm x 790 mm x 1,080 mm
Wheelbase	1,410 mm
Caster Angle	25.5 <sup>°</sup>
Trail	102 mm
Seat Height	785 mm
Ground Clearance	145 mm
Kerb Weight	189 kg
Fuel Tank Capacity	17.1 ℓ
SUSPENSION	

Suspension Type	Front: Telescopic, Pre-Load Adjustable
	Rear: Prolink Mono with 5 Stage Preload Ajuster, Swingarm

\*Colours and photos may vary from the actual product.

WHEELS AND BRAKE	
Rim Size	Front: 17M/C X MT 3.50
	Rear: 17M/C X MT 4.50
Tyres	Front: 120/70ZR17M/C (58W) (Tubeless)
	Rear: 160/60ZR17M/C (69W) (Tubeless)
Brakes Type	Front: Hydraulic Disc, ABS
	Rear: Hydraulic Disc, ABS
COLOUR VARIANT	
GRAND PRIX RED	MAT GUN POWDER BLACK METALLIC
PEARL METALLOID WHITE	

# The destination for riders Honda BigWing

Meet the various models of Honda BigBike And the world-class experience that can be yours at Honda BigWing, "The destination for riders."

#### All specifications are provisional and subject to change without notice.

- Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tyre pressure, installatio of accessories, cargo, rider and passenger
- These models come with a 2 year or 20,000km manufacturing warranty (whichever comes

### **[** Toll Free Line 1800 883993

Monday – Friday (9am – 5pm) Close on public holidays https://hondabigbike.com.my

Honda Motorcycle Malaysia

(a)

hondamotorcycle.my 012-499 3991

AUTHORISED DEALER STAMP